



	Existing Concrete
	New 4" thick concrete
	Hollad stone concrete paver "Winter Blend" color

General Notes

1. All existing asphalt shall be removed and disposed of properly.
2. Class 6 road base shall be imported and compacted to a thickness of 6" below pavers.
3. Curb cut into flow line for drainage pipe must be cleared with local authorities.
4. Concrete pavers shall match size and color of existing concrete pavers at plaza.
5. Glass tempered stamp shall be shown on all panes of glass.
6. New concrete shall be a minimum thickness of 4" @ 4,000psi strength.
7. All landscape damages due to construction access/staging will be repaired as back to 100% as before work started. (Take pictures to document existing site prior to work starting)
8. Owner shall be responsible for locating private utilities that are not marked by utility services where necessary.
9. Liquid propane tanks will be stored in a enclosed basin next to fire pit.
10. Polymeric sand 'tan' color shall be used as infill sand between paver joints.
11. Basalt water feature is to have auto water fill option tied into irrigation system. Pump shall sit in low portion of basin as designed with a flush out valve for wintenzation.

No.	Revision/Issue	Date

Firm Name and Address
South-Side Lawn & Landscape
 2114 S. Prairie Ave.
 Pueblo, CO. 81005
 P: 719.564.0858
 F: 719.564.5623



Project Name and Address
Bent County HealthCare Center
 810 Third St.
 Las Animas, CO. 81054
 P: 719-456-1340

Project	Sheet
Date	6.7.2017
Scale	N.T.S.